

Pack à porter.

The most innovative secondary packaging machinery.

Versatile. Fast. Eco-friendly.





Packaging material thickness:

Polyethylene (PE): from 35 to 90 My (microns) Density 0,87/0,93:

Different film thickness TBD

Max. poly reel diameter: Up to 450 mm

Max. poly reel width: Up to 2500 mm

Change-over time:

Max. 25 min. - based on staff training and performances.

Operating panel HMI

Boom mounted rotating "HMI" enabling machine control and management. The system allows to:

- ✓ Monitor technical functions, check them and adjust them for optimum performance.
- ✓ Store format parameters in order to facilitate format changeovers.
- ✓ Detect the trouble shooting machine diagnostics.
- ✓ In English and Italian (on request in addition the customer's language)



Width	380 mm - 850 mm (with ACTIVE PULL TECH 240 mm - 600mm)
Length	380 mm - 850 mm or 1200* mm
Heigth	180 mm - 400 mm
Overlapping	50/60 mm
Pitch (length)	max 1400 mm
Handle (optional)	50/60 mm
Max Reel (width)	2500 mm

Product handling:

With robot ABB IRB 1200 6 axes (diapers adult & babu)

Collating unit (tissue roll)

Bundle Speed:

Up to 22 cycles/min

*Up to 10 cycles/min with a double stroke insertion sequence.

NB: Production speed depends on the quality of the product coming from up-stream, on packaging material characteristics and final bundle dimensions required.










4.0 TECHNOLOGY

SUGGESTED FLOOR PLAN

Diapers



Tissue

